

LED MINIATURE ALPHANUMERIC ROUTE INDICATOR

SIGNAL
HOUSE
LIMITED



- **Network Rail Approved**
[PA05/03162 - Iss. 5]
- **Readability Category 3 - 100m**
- **Single and Double Sided**
- **Stacked units available**
- **Zero Maintenance**
- **LED Illuminator Lightsource [086/001285]**



The new Signal House Miniature Alphanumeric Route Indicator [MARI] range of signals are the industry leading solution for 'Stencil' applications. The new range offers the industry the only Cat 3 [100m] readable solution whilst continuing to offer a reliable LED light source, standard sized housings and full compliance to GK/RT/0045 and BR1651/2.

The signal incorporates the LED Light Source, Signal House LED Illuminator, using solid state components. The LED light source provides a crisp and readable display at a minimum of 100 meters, utilising fibre optic technology.

The Signal House MARI has demonstrated exceptional anti-phantom capabilities and suffers no detrimental performance due to direct sunlight.

Operating Voltage Range: 88 - 121V AC

Case Sizes: Single Sided - 500W X 300H X 680L
Double Sided - 500W X 300H X 1300L

Environment: IP54

Weight: Single Sided <30KG. Double Sided <45KG

Aspects: Max 3 Aspects

PART NUMBER	CAT NUMBER	DESCRIPTION	READING DISTANCE
X14100-***	0086/001414	LED MARI, 110V, SINGLE SIDED, DISPLAY TO BE SPECIFIED	Cat 3 - 100m
X14200-***	0086/001415	LED MARI, 110V, DOUBLE SIDED, DISPLAY TO BE SPECIFIED	Cat 3 - 100m
X14100-001	0086/001417	LED MARI, 110V, SINGLE SIDED, "OFF"	Cat 3 - 100m
X14100-002	0086/001416	LED MARI, 110V, SINGLE SIDED, "RA"	Cat 3 - 100m
X14100-003	0086/001418	LED MARI, 110V, SINGLE SIDED, "CD"	Cat 3 - 100m
X14100-004	0086/001419	LED MARI, 110V, SINGLE SIDED, "CD + RA"	Cat 3 - 100m
X14200-001	0086/001407	LED MARI, 110V, DOUBLE SIDED, "OFF".	Cat 3 - 100m
SPARES			
1814	0086/001285	LED ILLUNIMATOR	N/A

SIGNAL HOUSE LTD

CHERRYCOURT WAY, STANBRIDGE ROAD, LEIGHTON BUZZARD, BEDFORDSHIRE, LU7 4UH

TEL: 01525 377477

WWW.SIGNALHOUSEGROUP.CO.UK

SALES@SIGNALHOUSE.CO.UK